

# IES LM-79-08

## MEASUREMENT AND TEST REPORT

For

### ATG Electronics Corp.

9020 Rancho Park Court Rancho Cucamonga, CA 91730

**Test Model: LIFI-50F-4FT**

<b>Report Type:</b>	Electrical and Photometric tests including: Input Current, Power, Power Factor, Luminous Flux, Luminous Efficacy, CRI, CCT, Chromaticity Coordinate, Spectral Power Distribution
<b>Test Engineer:</b>	Carl Du <i>Carl Du</i>
<b>Report Number:</b>	RSZ161123530-10A2-M1
<b>Test Date:</b>	2016-11-27
<b>Report Date:</b>	2016-12-08
<b>Reviewed By:</b>	Blake Zhang / EE Engineer <i>Blake Zhang</i>
<b>Revised Note:</b>	The previous report RSZ161123530-10A2 is replaced by this report on 2016-12-08
<b>Prepared By:</b>	Bay Area Compliance Laboratories Corp. (Dongguan). Pu Long Cun 69, Puxinghu Industrial Area, Tangxia Town, Dongguan, Guangdong, P.R.China. Tel: +86-0769-86858888 Fax: +86-0769-86858588
<b>Accreditation:</b>	The IAS Accreditation Number TL-460.

## 1. Product Description

### General Information:

One sample was received on 2016-11-23 and used for testing.

Model Tested: LIFI-50F-4FT  
 Manufacturer: ATG Electronics Co.,Ltd  
 Brand Name: ATG  
 Product Designation: Direct Linear Ambient Luminaires  
 Burning Time Before Test: 0hour(For New Products)  
 Length: 4ft

### Rated Values:

Rated Voltage/Frequency: 120-277 V AC 50/60Hz  
 Rated Power: 40W  
 Nominal CCT: 5000K  
 Nominal Lumen Output: 4800lm

## 2. Standards Used

- IES LM-79-08: Approved Method: Electrical & Photometric Measurement of Solid-state Lighting Products
- ANSI C82.77-2002: Harmonic Emission Limits – Related Power Quality Requirements for Lighting
- IES TM-30-15: IES Method for Evaluating Light Source Color Rendition (This method is not in IAS accreditation scope)

## 3. Description of Test Equipment

Device	Manufacture	Model No	Serial No	Test Range	Calibration date	Calibration due date
Integrating Sphere	SENSING	SPR-600	S09008	25~50°C	2016-03-10	2017-03-09
High Accuracy Array spectroradiometer	EVERFINE	HAAS-2000	M112048CA1361125	380-780nm	2016-07-08	2017-07-07
Power meter	YOKOGAWA	WT310	C20E17024V	2kV/20A	2016-07-08	2017-07-07
DC Power Supply	ITECH	IT6154	0061 0417 6471 0010 19	0~32V	2016-03-04	2017-03-03
Thermal Meter	SENSING	N/A	N/A	25、50°C	2016-03-10	2017-03-09
Standard Light Source	SENSING	N/A	LSD090808	N/A	2016-09-24	2017-09-23
AC Power Supply	ALL Power	APW-105N	970613	220V±10% 50Hz	2016-03-04	2017-03-03

Statement of Traceability: Bay Area Compliance Laboratories Corp. (Dongguan) attested that all calibration has been performed using suitable standards traceable to National Primary Standards and International System of Units (SI).

## 4. Test Method

Product was tested with no seasoning. All stabilization and measurements were made in compliance with IES LM-79-08. The product was operated at rated voltage or at voltage required by manufacturer. The ambient temperature of the sample was maintained at 25°C±1°C during measurement. And relative humidity is less than 65%.

### **Integrating Sphere System**

The system includes AC power source, digital power meter, DC power supply, Spectroradiometer, and integrating sphere. The integrating sphere system is calibrated by standard spectrum light source before measurement.

4 $\pi$  geometry was used during measurement. The product was operated in its intended orientation in application and was recorded in this report.

The uncertainty of the light output (luminous flux) measurements is  $U=2.1\%$  ( $K=2$ ), at the 95% confidence level. The uncertainty of the correlated color temperature measurements is  $U=32K$  ( $K=2$ ), at the 95% confidence level. The uncertainty of the CRI is  $U=2.1$  ( $K=2$ ), at the 95% confidence level.

The uncertainty of power meter AC current  $U=0.19\%$  of rdg, AC Voltage  $U=0.15\%$  of rdg, Power  $U=0.20\%$  ( $K=2$ ), at the 95% confidence level.

### **Fidelity Index and Gamut Index Calculation**

The  $R_i$ ,  $R_g$  was calculated according to IES TM-30-15 by using calculation tools. The calculation was based on the measured SPD from 380nm to 780nm with 1nm intervals. All the colors in this report is for reference only.

FINAL

## 5. Test Result

### [Integrating Sphere System]

Total operating time for integrating sphere test: **1.0 hour**

Test orientation: **Downward**


### Photometric and Electrical Measurement Result

Voltage (V)	Frequency (Hz)	Current (A)	Power (W)	Power Factor	Luminous Flux(lm)	Efficacy (lm/W)
120.0	60	0.3502	41.71	0.9923	5017.2	120.29

Radiant Flux (W)	CCT (K)	Duv	x	y	u'	v'
15.444	4965	0.00305	0.3467	0.3590	0.2096	0.4885

### Color Rendering Index


<b>Ra</b>			
<b>83.0</b>			
<b>R1</b>	<b>R2</b>	<b>R3</b>	<b>R4</b>
81	90	95	80
<b>R5</b>	<b>R6</b>	<b>R7</b>	<b>R8</b>
81	86	86	65
<b>R9</b>	<b>R10</b>	<b>R11</b>	<b>R12</b>
4	77	79	57
<b>R13</b>	<b>R14</b>	<b>R15</b>	
84	98	75	




### Fidelity Index and Gamut Index

Fidelity Index $R_f$	81
Gamut Index $R_g$	93


### Spectral Power Distribution Comparison




### Plot of $R_g$ versus $R_f$




Chroma Shift by Hue




$R_f$  by Hue




Color Vector Graphic



### Color Fidelity by CES Sample



### Relative Spectral Power Distribution




nm	mW	nm	mW	nm	mW	nm	mW	nm	mW
380	1.761E+00	421	3.915E+00	462	7.896E+01	503	5.197E+01	544	7.043E+01
381	1.848E+00	422	4.509E+00	463	7.544E+01	504	5.295E+01	545	7.084E+01
382	1.356E+00	423	5.055E+00	464	7.200E+01	505	5.390E+01	546	7.098E+01
383	1.453E+00	424	5.737E+00	465	6.941E+01	506	5.489E+01	547	7.141E+01
384	1.386E+00	425	6.445E+00	466	6.674E+01	507	5.574E+01	548	7.160E+01
385	1.144E+00	426	7.357E+00	467	6.416E+01	508	5.653E+01	549	7.193E+01
386	1.039E+00	427	8.278E+00	468	6.166E+01	509	5.733E+01	550	7.222E+01
387	8.324E-01	428	9.426E+00	469	5.924E+01	510	5.799E+01	551	7.253E+01
388	6.230E-01	429	1.069E+01	470	5.660E+01	511	5.869E+01	552	7.277E+01
389	7.581E-01	430	1.207E+01	471	5.403E+01	512	5.954E+01	553	7.307E+01
390	6.657E-01	431	1.359E+01	472	5.113E+01	513	6.019E+01	554	7.342E+01
391	7.581E-01	432	1.521E+01	473	4.869E+01	514	6.091E+01	555	7.372E+01
392	6.762E-01	433	1.712E+01	474	4.607E+01	515	6.142E+01	556	7.405E+01
393	5.751E-01	434	1.935E+01	475	4.396E+01	516	6.200E+01	557	7.428E+01
394	6.060E-01	435	2.179E+01	476	4.213E+01	517	6.245E+01	558	7.455E+01
395	6.013E-01	436	2.444E+01	477	4.061E+01	518	6.307E+01	559	7.496E+01
396	5.377E-01	437	2.766E+01	478	3.952E+01	519	6.332E+01	560	7.532E+01
397	5.904E-01	438	3.120E+01	479	3.851E+01	520	6.386E+01	561	7.570E+01
398	5.768E-01	439	3.548E+01	480	3.790E+01	521	6.416E+01	562	7.582E+01
399	5.635E-01	440	3.995E+01	481	3.735E+01	522	6.464E+01	563	7.629E+01
400	6.435E-01	441	4.551E+01	482	3.734E+01	523	6.504E+01	564	7.657E+01
401	5.700E-01	442	5.155E+01	483	3.717E+01	524	6.532E+01	565	7.685E+01
402	5.663E-01	443	5.835E+01	484	3.722E+01	525	6.556E+01	566	7.710E+01
403	5.839E-01	444	6.609E+01	485	3.748E+01	526	6.593E+01	567	7.767E+01
404	6.577E-01	445	7.475E+01	486	3.778E+01	527	6.606E+01	568	7.776E+01
405	7.042E-01	446	8.366E+01	487	3.821E+01	528	6.647E+01	569	7.800E+01
406	7.722E-01	447	9.324E+01	488	3.857E+01	529	6.676E+01	570	7.828E+01
407	7.995E-01	448	1.022E+02	489	3.898E+01	530	6.703E+01	571	7.873E+01
408	9.387E-01	449	1.108E+02	490	3.964E+01	531	6.711E+01	572	7.898E+01
409	9.338E-01	450	1.180E+02	491	4.013E+01	532	6.742E+01	573	7.921E+01
410	9.945E-01	451	1.235E+02	492	4.089E+01	533	6.758E+01	574	7.947E+01
411	1.142E+00	452	1.266E+02	493	4.171E+01	534	6.790E+01	575	7.964E+01
412	1.331E+00	453	1.269E+02	494	4.261E+01	535	6.808E+01	576	7.980E+01
413	1.449E+00	454	1.248E+02	495	4.352E+01	536	6.832E+01	577	8.012E+01
414	1.665E+00	455	1.209E+02	496	4.447E+01	537	6.862E+01	578	8.024E+01
415	1.849E+00	456	1.155E+02	497	4.553E+01	538	6.898E+01	579	8.034E+01
416	2.090E+00	457	1.090E+02	498	4.660E+01	539	6.913E+01	580	8.045E+01
417	2.397E+00	458	1.020E+02	499	4.763E+01	540	6.931E+01	581	8.057E+01
418	2.706E+00	459	9.526E+01	500	4.891E+01	541	6.960E+01	582	8.066E+01
419	3.030E+00	460	8.909E+01	501	4.974E+01	542	6.990E+01	583	8.082E+01
420	3.462E+00	461	8.360E+01	502	5.100E+01	543	7.012E+01	584	8.084E+01




nm	mW	nm	mW	nm	mW	nm	mW	nm	mW
585	8.092E+01	626	5.818E+01	667	2.225E+01	708	6.356E+00	749	1.873E+00
586	8.083E+01	627	5.718E+01	668	2.161E+01	709	6.188E+00	750	1.814E+00
587	8.079E+01	628	5.628E+01	669	2.101E+01	710	6.006E+00	751	1.724E+00
588	8.092E+01	629	5.522E+01	670	2.048E+01	711	5.801E+00	752	1.717E+00
589	8.072E+01	630	5.420E+01	671	1.980E+01	712	5.590E+00	753	1.652E+00
590	8.070E+01	631	5.328E+01	672	1.939E+01	713	5.413E+00	754	1.620E+00
591	8.065E+01	632	5.232E+01	673	1.874E+01	714	5.257E+00	755	1.577E+00
592	8.057E+01	633	5.120E+01	674	1.819E+01	715	5.084E+00	756	1.541E+00
593	8.017E+01	634	5.026E+01	675	1.771E+01	716	4.950E+00	757	1.515E+00
594	7.994E+01	635	4.926E+01	676	1.714E+01	717	4.798E+00	758	1.508E+00
595	7.985E+01	636	4.818E+01	677	1.667E+01	718	4.685E+00	759	1.440E+00
596	7.931E+01	637	4.727E+01	678	1.616E+01	719	4.546E+00	760	1.418E+00
597	7.909E+01	638	4.634E+01	679	1.580E+01	720	4.406E+00	761	1.364E+00
598	7.866E+01	639	4.522E+01	680	1.523E+01	721	4.251E+00	762	1.350E+00
599	7.825E+01	640	4.432E+01	681	1.478E+01	722	4.103E+00	763	1.336E+00
600	7.776E+01	641	4.330E+01	682	1.433E+01	723	4.007E+00	764	1.264E+00
601	7.733E+01	642	4.238E+01	683	1.393E+01	724	3.896E+00	765	1.231E+00
602	7.696E+01	643	4.140E+01	684	1.353E+01	725	3.790E+00	766	1.226E+00
603	7.640E+01	644	4.044E+01	685	1.316E+01	726	3.635E+00	767	1.188E+00
604	7.595E+01	645	3.951E+01	686	1.272E+01	727	3.565E+00	768	1.167E+00
605	7.529E+01	646	3.861E+01	687	1.231E+01	728	3.407E+00	769	1.125E+00
606	7.475E+01	647	3.769E+01	688	1.197E+01	729	3.350E+00	770	1.114E+00
607	7.406E+01	648	3.691E+01	689	1.160E+01	730	3.229E+00	771	1.074E+00
608	7.353E+01	649	3.591E+01	690	1.128E+01	731	3.147E+00	772	1.054E+00
609	7.289E+01	650	3.503E+01	691	1.086E+01	732	3.039E+00	773	1.029E+00
610	7.230E+01	651	3.425E+01	692	1.059E+01	733	2.936E+00	774	1.020E+00
611	7.145E+01	652	3.338E+01	693	1.026E+01	734	2.856E+00	775	1.014E+00
612	7.071E+01	653	3.245E+01	694	9.947E+00	735	2.786E+00	776	9.835E-01
613	7.001E+01	654	3.166E+01	695	9.612E+00	736	2.702E+00	777	9.715E-01
614	6.909E+01	655	3.091E+01	696	9.362E+00	737	2.614E+00	778	9.345E-01
615	6.832E+01	656	3.010E+01	697	9.087E+00	738	2.556E+00	779	9.119E-01
616	6.744E+01	657	2.934E+01	698	8.804E+00	739	2.484E+00	780	9.136E-01
617	6.659E+01	658	2.854E+01	699	8.470E+00	740	2.411E+00		
618	6.575E+01	659	2.770E+01	700	8.230E+00	741	2.340E+00		
619	6.484E+01	660	2.705E+01	701	8.040E+00	742	2.312E+00		
620	6.389E+01	661	2.630E+01	702	7.738E+00	743	2.191E+00		
621	6.294E+01	662	2.557E+01	703	7.456E+00	744	2.153E+00		
622	6.211E+01	663	2.494E+01	704	7.272E+00	745	2.070E+00		
623	6.100E+01	664	2.420E+01	705	7.046E+00	746	2.032E+00		
624	6.012E+01	665	2.359E+01	706	6.827E+00	747	1.944E+00		
625	5.912E+01	666	2.292E+01	707	6.609E+00	748	1.906E+00		


CIE 1931 x y Chromaticity Diagram



7-Step Chromaticity Quadrangles



## 6. Product Photo



## 7. Report Revision

Report Number	Report Date	Contents
RSZ161123530-10A2	2016-12-02	Original report.
RSZ161123530-10A2-M1	2016-12-08	Update the test model number.

\*\*\*\*\*END OF REPORT\*\*\*\*\*