



# PSC-SGW-101-DC

## TruBlu Gateway

Product Card

Date: March 20, 2020	Ver 1.1
----------------------	---------



Fig.1 PSC-SGW-101-DC sample image



Technology Partner Silvair

## Overview

The **PSC-SGW-101-DC** is the TruBlu™ gateway that extends the mesh network with Internet access. It allows our partners to collect data from their Bluetooth mesh lighting networks and transmit them to the TruBlu™ Cloud, from where it can be visualised and analysed. The PSC-SGW-101-DC also allows the partners to have control over lighting control functions.

## Lighting installations with PSC-SGW-101-DC

- One gateway can control multiple areas
  - A single area is a single level of a building and includes a floor plan which helps to navigate through commissioning, monitoring and maintenance of a project.
- Can handle data from a network of approximately 200 bluetooth mesh devices.
- Works with qualified Bluetooth mesh stack.

---

## Specifications

<b>Computing &amp; Storage</b>	✓ 800 MHz ARM A7 with 512 MB RAM ✓ 8 GB of storage
<b>Ethernet</b>	✓ 10/100 Ethernet with PoE 802.3 af
<b>Wi-Fi</b>	✓ Wi-Fi 802.11a/b/g/n/ac
<b>Accessory Options</b>	✓ Wall / Ceiling Bracket ✓ International Power Adapter

---

## Services

The PSC-SGW-101-DC is the enabler of ATG services such as:

<b>Scheduling</b>	Automatic mode allowing to recall scheduled scenes for a zone(s) at the specified time on specified days.
<b>Energy Monitoring</b>	Provides real time data on the power consumption of the lighting installation in your building.
<b>Occupancy Monitoring</b>	See real-time occupancy heatmap.

---

### Remote maintenance and upgrades

- The PSC-SGW-101-DC is remotely upgradeable (regular maintenance updates).
- Remote access to gateway data, remote monitoring, remote provisioning. The owner of the lighting installation needs only to install the gateway in the space, but does not need to perform health-checks or do the updates.
- Monitoring and logging alerts for the key performance metrics such as: CPU load and connectivity status.
- In case of an unexpected issue with a gateway device or a need of an emergency reconfiguration, the owner / installer needs to contact the support and these cases are handled by the gateway provider.

---

### Updates and security

- Linux Operating System, secure boot & encrypted file system
- High level of hardware and software security (secure boot & encrypted file system that can only be accessed with the management platform)
- Secure provisioning of devices: gateways are provisioned with secure IDs and encrypted keys
- Automatic security updates
- OS updates & fixes to vulnerabilities as soon as any discovered

---

### Networking options

- Qualified Bluetooth Mesh
- 10/100 Ethernet with PoE 802.3 af
- Outbound and inbound amplification increasing connectivity range
- WiFi
- Static IP

---

### Gateway network requirements

- PSC-SGW-101-DC uses DHCP to configure its IP address, default gateway, and DNS servers.
- The PSC-SGW-101-DC user must white list several remote hosts & ports. A full list of remote hosts & ports is available
  - Be aware that many of these hosts resolve to multiple IP addresses which may change at any time. System administrators should not rely on white listing individual IP addresses for these services.

## Technical Specifications

<b>Features &amp; application</b>	An IoT gateway for the connection and management of Bluetooth mesh networks in commercial building applications. Access is via Silvar Commissioning, It delivers: Internet connectivity. Data collection - i.e. routing data from the network to the TruBlu™ Cloud. Future functionality: Management (recommissioning) & control of lighting networks. Future functionality: System status monitoring.
<b>Capacity &amp; performance</b>	The gateway provides full protection against power failure. The current hardware configuration allows the TruBlu Gateway to process 450 Bluetooth mesh network messages per second with data transfer reliability of over 99%.
<b>DC power supply</b>	12V, 1-1.5A or PoE 802.3 af
<b>Operating System</b>	Ubuntu Core
<b>Processor</b>	NXP i.MX6 UltraLite
<b>Communication protocols</b>	Bluetooth mesh, TCP/IP, IPv4
<b>Security</b>	Secure boot with encrypted operating system (to protect the integrity and confidentiality of the data) Secure communication with TruBlu Cloud over Internet (TLS) Secure communication with devices over Bluetooth Mesh
<b>RF information</b>	2.4 GHz BLE radio (IEEE 802.15.1) Tx/Rx Maximum radio frequency antenna power output: 10 mW (+10 dBm) Internal omni-directional trace antenna Communication range of 500m (over 1500 ft) line of sight
<b>Ports</b>	1 x RJ45 10/100 Ethernet port (with PoE option)
<b>Operating temperature</b>	0°C to +70°C 32 °F to 158 °F
<b>Housing &amp; Dimensions</b>	Material: ABS, PC 120 x 120 x 25 mm (4.7 x 4.7 x 1 inches)
<b>Weight</b>	0.254 kg (0.56 lbs )
<b>Mounting position</b>	Wall or surface mounted. As close to the geometrical centre of the lighting network as possible but as far as possible from potential sources of interference.
<b>Certifications</b>	FCC, IC, CE, RCM