

Decorative Emergency Light(DEL)



Product Description

The DEL Series can be applied in areas that are susceptible to rain and severe moisture, such as parking decks and outdoor commercial or residential applications. The fixture has a prismatic polycarbonate refractor with a durable die-cast aluminum housing available with durable powder coated finish.

Features

- Up to 138 LM/W Efficacy
- IP65, UL wet location listed
- Easy installation and maintenance
- 0-10V dimmable, with integrated photocell & EM Unit (90 minutes emergency operation)
- 120-277VAC universal input
- -40°C~45°C operation temperature, 0°C~45°C for EM operation temperature

Project Name:

Date:

Prepared By:

Notes:

Construction

- Die-cast aluminum housing, bronze finish comes standard, white and black optional (check with ours sales support for lead time)
- Prismatic polycarbonate lens

Electrical Performance

- 120-277VAC Universal Input
- 15W, with 5W emergency operation, power factor >0.9

Photometric Performance

- CCT Selectable comes standard (3500K-4000K-5000K), Ra>80
- Up to 138 LM/W Efficacy, around 2000 LM output

Operation Temperature

- -40°C~45°C operation temperature
- 0°C~45°C for EM operation temperature

Photocell and Emergency Unit

- 0-10V Dimmable
- Integrated photocell & EM Unit (90 minutes emergency operation)

Warranty

- ATG's guaranteed five (5) year warranty

Ordering Information:

Typical Order Example: DEL-15W-CS -PE1

Series	Wattage	CCT	Input Voltage	Dimming	Finish	Options
DEL	-15=15W	-CS=3500K/4000K/5000K Selectable	Blank=100-277VAC	Blank=1-10V Dimming -ND=Non-Dimming	-Blank=Bronze -WH=White -BL=Black	-PE=Photocell -PE1=Photocell+ 5W EM

* CCT selectable comes standard, 5W EM unit comes standard, bronze finish comes standard

* Check with sales and rep for lead time and stock info

Model	Wattage	Input Voltage	Efficacy	Lm Flux	CRI	CCT	PF	BUG	L70	Packing Info
DEL-15-CS	15W	120~277VAC	130LM/W	1740 LM	83	3500K	0.9	B1U3G1	50,000H	10.47*6.53*3.78in
			138LM/W	1814 LM	83	4000K				
			133LM/W	1775 LM	83	5000K				
Finish Color		Housing	Lens Type			Certification		Warranty		
Bronze, White, Black		Die Cast Aluminum	PC, Frosted			UL, DLC (Pending)		5 Years		



877.461.5333



sales@atgelectronics.com



atgledlighting.com