

CL16


CL16  
CYLINDER



CL 16 CYLINDER

DUO Selectable LED Cylinder

CLI6  
DUO Selectable LED Cylinder



DESCRIPTION

LED Cylinder | Can Light | Power & CCT Selectable | 120-277Vac |  
0-10V dimming | Ra>90 | Multiple Beam Spread | Optional Integrated BLE Mesh Module



PRODUCT FEATURES

- Low Profile, Low Glare, Low Flicker, Classic Design
- High Quality Cast Aluminum Housing, Replaces Halogen “Mini-Can” Fixtures
- Power & CCT Selectable
- Multiple Mounting Options (Stem Mount / Cable Mount / Ceiling Mount)
- 40° Beam Spread Refractor Comes Standard (20°, 30°and 50° Reflector Included Separately)
- Ambient Operating Temperature: -10°C(14°F)~40°C(104°F)
- THD<14%, Power Factor>0.9
- ATG Guaranteed 10 Year Warranty
- ETL Listed, Energy Star Listed

\* Optional Integrated BLE Mesh Module For Remote Dimming, ON/OFF Via App on PC, Laptop, iPhone, iPad  
\* L70 Hours>100,000

POWER AND COLOR TEMPERATURE SELECTABILITY

- Feature Color Selectable Technology: Adjust CCT between 3000K / 3500K / 4000K
- Feature Power Selectable Techology: Adjust wattage between 40W / 30W / 20W

APPLICATIONS

Houses of Worship, Schools, Auditoriums, Lobbies, Offices, Museum spaces


PRODUCT SPECIFICATIONS

Model Number	CCT	CRI	3000K			3500K			4000K		
			Wattage(W)	Efficacy(LM/W)	Lumens(LM)	Wattage(W)	Efficacy(LM/W)	Lumens(LM)	Wattage(W)	Efficacy(LM/W)	Lumens(LM)
CLI-50W-T1	3000K/3500K/ 4000K Select	>90	41	102	4,171	41	104	4,258	41	107	4,362
			30	105	3,151	30	107	3,217	30	110	3,296
			20	108	2,164	20	110	2,209	20	113	2,263

**CL16**  
DUO Selectable LED Cylinder

**PHOTOMETRIC SPECIFICATIONS**

**CLI6A-40W-T1 @4000K 20°**




**Zonal Lumen Summary**

Zone	Lumens	%Lamp	%Luminaire
0-30	4,021.0	92%	92.1%
0-40	4,233.9	96.9%	97%
0-60	4,349.4	99.5%	99.6%
60-90	16.8	0.4%	0.4%
0-90	4,366.1	99.9%	100%

**Illuminance At A Distance**

Height (M)	Center Beam	Beam Spread(M)		Field Spread(M)	
	Footcandle	Horizontal	Vertical	Horizontal	Vertical
1.00	18,829.16 LUX	0.4	0.4	0.8	0.8
2.00	4,707.29 LUX	0.9	0.9	1.6	1.6
3.00	2,092.13 LUX	1.3	1.3	2.4	2.4
4.00	1 176.82 LUX	1.7	1.7	3.2	3.3
5.00	753.17 LUX	2.2	2.1	4.0	4.1
6.00	523.03 LUX	2.6	2.6	4.8	4.9
		Beam Angle		Field Angle	
		24.5° 24.2°		43.9° 44.2°	

**CLI6A-40W-T1 @4000K 30°**




**Zonal Lumen Summary**

Zone	Lumens	%Lamp	%Luminaire
0-30	4,250.7	93.5%	93.6%
0-40	4,442.8	97.8%	97.8%
0-60	4,527.5	99.6%	99.7%
60-90	13.6	0.3%	0.3%
0-90	4,541.1	99.9%	100%

**Illuminance At A Distance**

Height (M)	Center Beam	Beam Spread(M)		Field Spread(M)	
	Footcandle	Horizontal	Vertical	Horizontal	Vertical
1.00	12,827.63 LUX	0.6	0.6	1.0	1.0
2.00	3,206.91 LUX	1.2	1.3	1.9	2.0
3.00	1,425.29 LUX	1.9	1.9	2.9	3.0
4.00	801.73 LUX	2.5	2.5	3.9	3.9
5.00	513.11 LUX	3.1	3.1	4.9	4.9
6.00	356.32 LUX	3.7	3.8	5.8	5.9
		Beam Angle		Field Angle	
		34.7° 34.7°		52.0° 52.5°	

**CLI6A-40W-T1 @4000K 40°**




**Zonal Lumen Summary**

Zone	Lumens	%Lamp	%Luminaire
0-30	3,975.6	91.1%	91.2%
0-40	4,237.4	97.1%	97.2%
0-60	4,358.8	99.9%	100%
60-90	1.7	0%	0%
0-90	4,360.5	100%	100%

**Illuminance At A Distance**

Height (M)	Center Beam	Beam Spread(M)		Field Spread(M)	
	Footcandle	Horizontal	Vertical	Horizontal	Vertical
1.00	8,596.72 LUX	0.8	0.7	1.1	1.1
2.00	2,149.18 LUX	1.6	1.5	2.3	2.2
3.00	955.19 LUX	2.3	2.2	3.4	3.3
4.00	537.30 LUX	3.1	2.9	4.6	4.4
5.00	344.08 LUX	3.9	3.7	5.7	5.5
6.00	238.95 LUX	4.7	4.4	6.8	6.6
		Beam Angle		Field Angle	
		42.5° 40.3°		59.3° 57.7°	

**CLI6A-40W-T1 @4000K 50°**



**Zonal Lumen Summary**




Zone	Lumens	%Lamp	%Luminaire
0-30	3,504.8	81.6%	81.7%
0-40	4,063.0	94.7%	94.7%
0-60	4,289.7	99.9%	100%
60-90	1.8	0%	0%
0-90	4,291.5	100%	100%

**Illuminance At A Distance**

Height (M)	Center Beam	Beam Spread(M)		Field Spread(M)	
	Footcandle	Horizontal	Vertical	Horizontal	Vertical
1.00	5,677.14 LUX	0.9	1.0	1.5	1.5
2.00	1,419.29 LUX	1.8	1.9	2.9	3.1
3.00	630.79 LUX	2.6	2.9	4.4	4.6
4.00	354.82 LUX	3.5	3.8	5.9	6.1
5.00	227.37 LUX	4.4	4.8	7.4	7.7
6.00	157.89 LUX	5.3	5.8	8.8	9.2
		Beam Angle		Field Angle	
		47.5° 51.3°		72.7° 74.9°	

**CLI6**  
DUO Selectable LED Cylinder

**PHYSICAL FEATURES**



1. Stem, ceiling and pendant mount available(Stem mount pictured)
2. 12" stem comes standard, 24", 48", 96" stem optional
3. Integrated BLE Mesh Control Available For Remote Dimming, On/Off Via App
4. Power and CCT Selectable, Multiple Beam Spread Available


## CLI6

DUO Selectable LED Cylinder

### ADDITIONAL ACCESSORIES (SOLD SEPARATELY)

Model Number	Description
HAC-CLI6-ST	Linkable Stem for Stem Mounting, 11.8 inch (30cm)
CAC-CLI6	Extension Power Cable for LED Cylinder, customized length
LEN-CLI6-20D	Lens for LED Cylinder, 20 degree
LEN-CLI6-30D	Lens for LED Cylinder, 30 degree
LEN-CLI6-50D	Lens for LED Cylinder, 50 degree

### PRODUCT DIMENSIONS



### ORDER FORMAT

Series	Wattage	CCT	Control	Finish	Mounting
<b>CLI6</b>	<b>40W</b>	<b>T1</b>			
CLI6	40W= 20W/30W/ 40W Selectable	T1= 3000K/3500K/ 4000K Selectable	Blank= w/o BLU module BL= w/ BLU module	-Blank =Black -W =White *	T= Stem Mount C= Ceiling Mount S= Suspension Mount

\*Black finish comes standard, extra lead time and cost may apply on white finish. Contact us for more details.