



LED lighting made easy.

# 2026 BUYER'S GUIDE

COMMERCIAL AND INDUSTRIAL  
LED LIGHTING



Email Us

Office #: (951)245-6222

10588 Monte Vista Ave, Montclair, CA 91763

<https://atgledlighting.com/>

[sales@atgledlighting.com](mailto:sales@atgledlighting.com)

Always Think **Green.**

# ATG

## ALWAYS THINK GREEN

● ATG Electronics provides top of the line LED lighting for lighting specifiers across the globe. ATG fixtures cover all commercial and industrial applications—including but not limited to warehouses, schools, parks, urban areas, parking garages, workshops, and offices. Our LED luminaires are assembled, warehoused and sold out of our US headquarters in Montclair, CA.

## FEATURES & LISTINGS

- |  |  |  |  |
|--|--|--|--|
|  | UL Listed                                |  | Motion Sensor Offered                              |
|  | Intertek ETL Listed                      |  | EM Driver Offered                                  |
|  | DLC Standard/<br>Premium V5.1 Listed     |  | Daylight Sensor/<br>Photocell Offered              |
|  |  |  |  |
|  | Energystar Compliant                     |  | Power & CCT Selectable                             |
|  | CEC Title 24 Compliant                   |  | Power Selectable                                   |
|  | 0-10V Dimming/1-10V Dimming              |  | CCT Selectable                                     |
|  | Wet Location Rated<br>IP65/IP66 or above |  | 5 Year/10 Year Warranty<br>See website for details |
|  |  |  |  |
|  | Dark Sky Listed                          |  | Bluetooth Mesh Control Offered                     |
|  | Beam Angle Field Adjustable              |  | SILVAIR System Compatible                          |
|  | BAA Optional                             |  | RELOC Wiring Offered                               |
|  |  |  | Keilton+Autani System Comptaible                   |

# TABLE OF CONTENTS



- 02 Brief Introduction
- 03 Features and Listings
- 04-05 Table of Contents

## 06-07 **Indoor LED Luminaires**

### **Warehouse Lighting**

- 08-09 Stellar Pro - Power Selectable High Heat Resistant Linear Highbay
- 10-11 Skyline G4- Power and CCT Selectable Contractor Linear Highbay
- 12-13 Helix G5- Power and CCT Selectable Round Highbay

### **Harsh and Hazardous Lighting**

- 14-15 HBZ-L1 - LED Linear Highbay for Hazardous Locations
- 16-17 HBZ-R1 - LED Round Highbay for Hazardous Locations

### **Ambient General Lighting**

- 18-19 DUO Panel G2E - Power and CCT Selectable Backlit Panel
- 20-21 DUO Troffer G3 - Power and CCT Selectable Recessed Troffer
- 22-23 DUO Direct Kit G2 - Power and CCT Selectable Retrofit Kit
- 24-25 Flint - CCT Selectable Flush Mount Luminaire

### **Linear Lighting**

- 26-27 Huron G4 - Power and CCT Selectable Architectural Linear Fixture
- 28-29 DUO LNS - Power and CCT Selectable Contractor Linear Fixture
- 30 WR3 - Power and CCT Selectable Wrap Light

### **Downlight**

- 31-32 DUO Downlight - Power and CCT Selectable Retrofit Downlight
- 33 ELD - CCT Selectable Residential Retrofit Downlight
- 34-35 CLI6 - Power and CCT Selectable Cylinder
- 36-37 EDF - CCT Selectable Fire Rated Wafer Downlight

### **Stairwell Lighting**

- 38-39 LSC - Power and CCT Selectable Cutoff Stairwell Fixture
- 40-41 LSD - Power and CCT Selectable Ultrasonic Stairwell Fixture

### **Vaportight and Emergency Lighting**

- 42-43 Atlas VPL - LED Vaportight Gasketed Fixture
- 44-45 Atlas VPM - LED Vaportight Gasketed Fixture
- 46-47 Exit Sign and Emergency Light

## 48-49 **Outdoor LED Luminaires**

### **Area and Parking Lot Lighting**

- 50-51 Archer G2 - Architectural Area Light/Flood Light Combination
- 52-53 Clio G2 - Power and CCT Selectable LED Post Top

### **Flood and Sports Lighting**

- 54-55 Forza - Beam Angle Adjustable Floodlight
- 56-57 Ultra SP8 - Power Selectable Sports Light
- 58-59 ACE - Power and CCT Selectable Tennis Court Sports Light
- 60-61 Vulvan V1 - High Mast Floodlight
- 62-63 Vulvan V2 - Round High Mast Floodlight

### **Wall Lighting**

- 64-65 Guard Pack G2 - Power and CCT Selectable LED Full Cutoff Wall Pack
- 66 DEL - Decorative Wall Pack with Emergency Battery Backup
- 67 ECWP - CCT Selectable Mini Wall Pack
- 68-69 WPDS - Power and CCT Selectable LED Open Face Wall Pack

### **Canopy and Garage Lighting**

- 70 Sector - Power and CCT Selectable Square Canopy Light
- 71 GRL - General Purpose Round Garage Light


### **Bollard**

- 72 Oceanside G3 - Power and CCT Selectable LED Bollard

## 73-74 **IES Footcandle Recommendations**



**INDOOR**  
**LED LUMINAIRES**



# Stellar Pro

## Power Selectable High Heat Resistant Linear Highbay




Part Number	HBST-155P-50-S	HBST-215P-50-S
Dimension	14.3"x11.1"	18.1"x11.8"
CRI	80	80
CCT	5000K*	5000K*
Beam Spread	95°x95° (40°x90° Optional)	95°x95° (40°x90° Optional)
Input Voltage	120-277V (347-480V Optional)	120-277V (347-480V Optional)
Wattage	155W/130W/110W Selectable	215W/180W/165W Selectable
Efficacy	156 LM/W+	158 LM/W+
Light Output	23,786 LM	33,605 LM
Dimming	0-10V	0-10V
L70	>208,000 Hrs	>208,000 Hrs



Part Number	HBST-320P-50-S	HBST-400P-50-S
Dimension	23.1"x11.8"	26.1"x13.4"
CRI	80	80
CCT	5000K*	5000K*
Beam Spread	95°x95° (40°x90° Optional)	95°x95° (40°x90° Optional)
Input Voltage	120-277V (347-480V Optional)	120-277V (347-480V Optional)
Wattage	320W/290W/255W Selectable	400W/360W/320W Selectable
Efficacy	158 LM/W+	158 LM/W+
Light Output	49,905 LM	63,199 LM
Dimming	0-10V	0-10V
L70	>208,000 Hrs	>208,000 Hrs

\*4000K also available. Extra lead time and cost may apply.


### PHYSICAL FEATURES



1. Emergency Backup Options Available\*
2. Die-Casting Aluminum Housing, Decreasing LED Junction Temperature, Ensuring Long Life and High Efficacy.
3. Sensor Receptacle Pre-Installed, Plug and Play Sensor Available
4. 90°x90° Optics For General Use, 40°x90° Optional For Aisle Distribution

\* Need extra driver box for mounting, sold separately.





# Skyline G4

## Power and CCT Selectable Contractor Linear Highbay



DLC  
V6.0



DLC  
V6.0

Part Number	HBELB-135P-TIF-R-G4	HBELC-200P-TIF-R-G4
Dimension	16.5"x10.2"	22.8"x10.2"
CRI	>80	>80
CCT	4000K/5000K Selectable	4000K/5000K Selectable
Beam Spread	40°x110° (40°x90° Optional)	40°x110° (40°x90° Optional)
Input Voltage	120-277V (347-480V Optional)	120-277V (347-480V Optional)
Wattage	135W/115W/100W Selectable	200W/185W/155W Selectable
Efficacy	154 LM/W+	153 LM/W+
Light Output	20,355 LM	28,759 LM
Dimming	0-10V	0-10V
L70	>132,000 Hrs	>132,000 Hrs



DLC  
V6.0



DLC  
V6.0


Part Number	HBELD-270P-TIF-R-G4	HBELC-400P-TIF-R-G4
Dimension	31.1"x10.2"	44.1"x10.2"
CRI	>80	>80
CCT	4000K/5000K Selectable	4000K/5000K Selectable
Beam Spread	40°x110° (40°x90° Optional)	40°x110° (40°x90° Optional)
Input Voltage	120-277V (347-480V Optional)	120-277V (347-480V Optional)
Wattage	270W/230W/200W Selectable	400W/340W/270W Selectable
Efficacy	155 LM/W+	151 LM/W+
Light Output	39,351 LM	60,384 LM
Dimming	0-10V	0-10V
L70	>134,000 Hrs	>134,000 Hrs

\*The fixture is already upgraded to meet DLC V6.0 requirements. Talk to sales team for submission schedule.

### ACCESSORIES



### LIGHT DISTRIBUTION



# Helix G5

## Power and CCT Selectable Round Highbay



DLC V6.0



Part Number	HBUF-150W-T1-G5
CRI	80
CCT	4000K/5000K Selectable
Input Voltage	120-277V (347-480V Optional)
Wattage	150W/120W/90W Selectable
Efficacy	155 LM/W
Light Output	23,250 LM
Dimming	0-10V
L70	>136,000 Hrs

DLC V6.0



Part Number	HBUF-240W-T1-G5
CRI	80
CCT	4000K/5000K Selectable
Input Voltage	120-277V (347-480V Optional)
Wattage	240W/200W/180W Selectable
Efficacy	155 LM/W
Light Output	37,200 LM
Dimming	0-10V
L70	>136,000 Hrs

DLC V6.0



Part Number	HBUF-300W-T1-G5
CRI	80
CCT	4000K/5000K Selectable
Input Voltage	120-277V (347-480V Optional)
Wattage	300W/240W/200W Selectable
Efficacy	155 LM/W
Light Output	46,500 LM
Dimming	0-10V
L70	>136,000 Hrs

\*The fixture is already upgraded to meet DLC V6.0 requirements.  
Talk to sales team for submission schedule.



# HBZ-L1

## LED Linear Highbay for Hazardous Locations



Part Number	HBZ-L1-40W-50
Optics	80°/110°
CRI	80
CCT	5000K*
Input Voltage	120-277V
Wattage	40W
Efficacy	134 LM/W
Light Output	5,401 LM
Finish	Grey/Yellow
Listings	UL/CID2 Group A,B,C,D
Mounting	Yoke/Ceiling/Pendant/Chain Mount
L70	>74,000 Hrs

\*Available with other CCT.



Part Number	HBZ-L1-80W-50
Optics	80°/110°
CRI	80
CCT	5000K*
Input Voltage	120-277V
Wattage	80W
Efficacy	144 LM/W
Light Output	11,399 LM
Finish	Grey/Yellow
Listings	UL/CID2 Group A,B,C,D
Mounting	Yoke/Ceiling/Pendant/Chain Mount
L70	>74,000 Hrs

\*Available with 277-480V.

\*Available with other CCT.



Part Number	HBZ-L1-120W-50
Optics	80°/110°
CRI	80
CCT	5000K*
Input Voltage	120-277V
Wattage	120W
Efficacy	128 LM/W
Light Output	15,582 LM
Finish	Grey/Yellow
Listings	UL/CID2 Group A,B,C,D
Mounting	Yoke/Ceiling/Pendant/Chain Mount
L70	>74,000 Hrs

\*Available with other CCT.



# HBZ-R1

## LED Round Highbay for Hazardous Locations



Part Number	HBZ-R1-30W-50
Lens	Flat Lens/80° Flat Lens/Sphere Lens/Drop Lens
CRI	80
CCT	5000K*
Input Voltage	120-277V
Wattage	30W
Efficacy	141 LM/W
Light Output	4,538 LM
Finish	Grey/Yellow
Listings	UL/CID2 Group A,B,C,D
L70	>74,000 Hrs

\*Available with other CCT.



Part Number	HBZ-R1-60W-50
Lens	Flat Lens/80° Flat Lens/Sphere Lens/Drop Lens
CRI	80
CCT	5000K*
Input Voltage	120-277V
Wattage	60W
Efficacy	140 LM/W
Light Output	8,275 LM
Finish	Grey/Yellow
Listings	UL/CID2 Group A,B,C,D
L70	>74,000 Hrs

\*Available with other CCT.



Part Number	HBZ-R1-100W-50
Lens	Flat Lens/80° Flat Lens/Drop Lens
CRI	80
CCT	5000K*
Input Voltage	120-277V
Wattage	100W
Efficacy	149 LM/W
Light Output	14,172 LM
Finish	Grey/Yellow
Listings	UL/CID2 Group A,B,C,D
L70	>74,000 Hrs

\*Available with other CCT.



Part Number	HBZ-R1-150W-50
Lens	Flat Lens/80° Flat Lens/Drop Lens
CRI	80
CCT	5000K*
Input Voltage	120-277V*
Wattage	150W
Efficacy	149 LM/W
Light Output	21,579 LM
Finish	Grey/Yellow
Listings	UL/CID2 Group A,B,C,D
L70	>74,000 Hrs

\*Available with 277-480V.

\*Available with other CCT.





# DUO Panel G2E

## Power and CCT Selectable Backlit Panel



Part Number	FPBL22-20W-T1-RU-E	FPBL14-20W-T1-RU-S	FPBL24-30W-T1-RU-E
CRI	80	80	80
CCT	3500K/4000K/5000K Selectable	3500K/4000K/5000K Selectable	3500K/4000K/5000K Selectable
Input Voltage	120-277V	120-277V	120-277V
Wattage	30W/25W/20W Selectable	30W/25W/20W Selectable	40W/35W/30W Selectable
Efficacy	137 LM/W+	137 LM/W+	131 LM/W+
Light Output	4,110 LM	4,110 LM	5,240 LM
L70	>100,000 Hrs	>100,000 Hrs	>100,000 Hrs

### Bluetooth Control



### Accessories


Bluetooth Mesh  
PIR Sensor




120VAC 2-Button  
Dimmer Wall Switch



Emergency Battery  
Backup Kit



Surface Mount Kit





# DUO Troffer G3

## Power and CCT Selectable Recessed Troffer



Part Number	ECRT14-30W-T2-G3
CRI	80
CCT	3000K/3500K/4000K/5000K/6500K Selectable
Input Voltage	120-277V
Wattage	30W/25W/18W/15W Selectable
Efficacy	150 LM/W+
Light Output	4,500 LM
L70	>100,000 Hrs



Part Number	ECRT22-30W-T2-G3
CRI	80
CCT	3000K/3500K/4000K/5000K/6500K Selectable
Input Voltage	120-277V
Wattage	30W/25W/18W/15W Selectable
Efficacy	150 LM/W+
Light Output	4,500 LM
L70	>100,000 Hrs



Part Number	ECRT24-41W-T2-G3
CRI	80
CCT	3000K/3500K/4000K/5000K/6500K Selectable
Input Voltage	120-277V
Wattage	41W/34W/28W/20W Selectable
Efficacy	150 LM/W+
Light Output	6,150 LM
L70	>100,000 Hrs

\*The fixture is already upgraded to meet DLC V6.0 requirements. Talk to sales team for submission schedule.

### Accessories


Bluetooth Mesh PIR Sensor




120VAC 2-Button Dimmer Wall Switch



Emergency Battery Backup Kit



Surface Mount Kit





# DUO Direct Kit G2

## Power and CCT Selectable Retrofit Kit



Part Number	ECDK22-20W-TI-R0-R1
CRI	80
CCT	3500K/4000K/5000K
Input Voltage	120-277V
Wattage	30W/25W/20W Selectable
Efficacy	139 LM/W+
Light Output	3,925 LM
L70	>100,000 Hrs



Part Number	ECDK24-25W-TI-R0-R1
CRI	80
CCT	3500K/4000K/5000K
Input Voltage	120-277V
Wattage	35W/30W/25W Selectable
Efficacy	139 LM/W+
Light Output	4,519 LM
L70	>100,000 Hrs

### Accessories


Bluetooth Mesh  
PIR Sensor




120VAC 2-Button  
Dimmer Wall Switch



Emergency Battery  
Backup Kit



Surface Mount Kit



# Flint

## CCT Selectable Flush Mount Luminaire



Part Number	FLT5-8W-T2
Dimension	Ø5.3"*3.7"
CRI	80
CCT	2700K/3000K/3500K/4000K/5000K Selectable
Input Voltage	120V
Wattage	8W
Efficacy	58 LM/W
Light Output	459 LM
Dimming	TRIAC
Options	-
L70	>100,000 Hrs

Part Number	FLT7-12W-T2	FLT7-12W-T2-SE
Dimension	Ø7.1"*5.5"	Ø6.5"*4.8"
CRI	80	80
CCT	2700K/3000K/3500K/4000K/5000K Selectable	2700K/3000K/3500K/4000K/5000K Selectable
Input Voltage	120V	120V
Wattage	12W	12W
Efficacy	62LM/W	62LM/W
Light Output	752LM	752LM
Dimming	TRIAC	-
Options	EM	Integrated Sensor/EM
L70	>100,000 Hrs	>100,000 Hrs


Part Number	FLT9-18W-T2	FLT9-18W-T2-SE
Dimension	Ø8.9"*7.2"	Ø8.9"*6.9"
CRI	80	80
CCT	2700K/3000K/3500K/4000K/5000K Selectable	2700K/3000K/3500K/4000K/5000K Selectable
Input Voltage	120V	120V
Wattage	18W	18W
Efficacy	63LM/W	63LM/W
Light Output	1,142LM	1,142LM
Dimming	TRIAC	-
Options	EM	Integrated Sensor/EM
L70	>100,000 Hrs	>100,000 Hrs

Part Number	FLT12-24W-T2	FLT12-24W-T2-SE
Dimension	Ø11.8"*10.2"	Ø12.1"*9.8"
CRI	80	80
CCT	2700K/3000K/3500K/4000K/5000K Selectable	2700K/3000K/3500K/4000K/5000K Selectable
Input Voltage	120V	120V
Wattage	24W	24W
Efficacy	95LM/W	95LM/W
Light Output	2,225LM	2,225LM
Dimming	TRIAC	-
Options	-	Integrated Sensor
L70	>100,000 Hrs	>100,000 Hrs



# Huron G4

## Power and CCT Selectable Architectural Linear Fixture



Part Number	LIF12-24-PIU-G4	LIF14-50-PIU-G4	LIF18-72-PIU-G4
Length	2FT	4FT	8FT
CRI	>80		
CCT	3000K/3500K/4000K/5000K/6500K Selectable		
Input Voltage	120-277V	120-277V	120-277V
Wattage	24W/20W/16W/12W/8W Selectable	50W/40W/35W/30W/25W Selectable	72W/60W/50W/40W/30W Selectable
Efficacy	125LM/W+	125LM/W+	125LM/W+
Light Output	2,970 LM	6,099 LM	9,234 LM
Distribution	100% Down / 70% Down & 30% Up / 50% Down & 50% Up / 30% Down & 70% Up / 100% Up		
L70	>100,000 Hrs	>100,000 Hrs	>100,000 Hrs

\*The fixture is already upgraded to meet DLC V6.0 requirements. Talk to sales team for submission schedule.


### Mounting Options



Suspension Mount



Surface Mount



Wall Mount

### TRI-Selectable



5 Wattage, 5 CCT, 5 Distribution

### Linking Pattens



X Connector



T Connector



L Connector



# LNS G3

## Power and CCT Selectable Linear Fixture



Part Number	LNS2-25-TI-B-Rx-G3	LNS2-25-TI-W-Rx-G3
Length	2FT	
CRI	>80	
CCT	3000K/4000K/5000K Selectable	
Input Voltage	120-277V	
Wattage	25W/20W/15W Selectable	
Efficacy	141LM/W+	
Max Output	3,671 LM	
L70	>190,000 Hrs	



Part Number	LNS4-40-TI-B-Rx-G3 LNS4-40-TI-W-Rx-G3	LNS4-65-TI-B-Rx-G3 LNS4-65-TI-W-Rx-G3
Length	4FT	
CRI	>80	
CCT	3000K/4000K/5000K Selectable	
Input Voltage	120-277V	
Wattage	40W/30W/25W Selectable	
Efficacy	146LM/W+	
Max Output	5,931 LM	
L70	>190,000 Hrs	



Part Number	LNS8-65-TI-B-Rx-G3 LNS8-65-TI-W-Rx-G3	LNS8-90-TI-B-Rx-G3 LNS8-90-TI-W-Rx-G3
Length	8FT	
CRI	>80	
CCT	3000K/4000K/5000K Selectable	
Input Voltage	120-277V	
Wattage	65W/60W/55W Selectable	
Efficacy	146LM/W+	
Max Output	9,729 LM	
L70	>190,000 Hrs	

\*The fixture is already upgraded to meet DLC V6.0 requirements. Talk to sales team for submission schedule.  
\*Fixture available in curved lens and batten lens.



Both standalone sensor and Bluetooth sensor are optional.



Emergency Battery Backup



PIR Sensor





# WR3

## Power and CCT Selectable Wrap Light

Part Number	WR3-4FT-30-T1-F
Dimension	4FT
CRI	>80
CCT	3500K/4000K/5000K Selectable
Input Voltage	120-277V
Wattage	40W/35W/30W Selectable
Efficacy	130 LM/W
Light Output	5,280 LM
Dimming	0-10V
L70	>100,000 Hrs



# DUO Downlight

## Power and CCT Selectable Retrofit Downlight




Part Number	SP8-40P-50-M	SP8-50P-50-M	SP8-60P-50-M
Dimension	Ø4"	Ø6"	Ø8"
CRI	>80	>80	>80
CCT	2700K/3000K/3500K/4000K/5000K Selectable		
Input Voltage	120-277V	120-277V	120-277V
Wattage	6W/8W/10W/12W/16W Selectable	12W/16W/22W/26W/30W Selectable	16W/22W/26W/30W/35W Selectable
Efficacy	100 LM/W+	100 LM/W+	100 LM/W+
Light Output	1,600 LM	3,000 LM	3,500 LM
Dimming	0-10V	0-10V	0-10V
L70	>50,000 Hrs	>50,000 Hrs	>50,000 Hrs

**Power Box**  
- PC material  
- Internal flicker free driver  
- 0-10V dimming

**Spring installation**  
Can be installed in the junction box or can.



**POWER SELECT ADJUSTMENT SWITCH**  
5 wattage selection available



Flexible steel conduit with 1/2" KO (3/8" Trade Size) snap in connector.

**COLOR SELECT ADJUSTMENT SWITCH**  
Set dip switch to adjust CCT between 2700K, 3000K, 3500K, 4000K, and 5000K.



- Front IP54  
- Aluminum lamp body  
- Deep reflector design  
- Low glare



## Accessories



Goof Ring 4"



Goof Ring 6"



Goof Ring 8"



Emergency Battery Backup



New Construction Plate for T-Grid Ceiling



New Construction Plate for Stud&Joist Ceiling

# ELD

## CCT Selectable Residential Retrofit Downlight



Part Number	ELD4-9-5CCT-W-SM	ELD4-9-5CCT-W-BF
Dimension	Ø4"	
Trim	Smooth	Baffle
CRI	>90	
CCT	2700K/3000K/3500K/4000K/5000K Selectable	
Input Voltage	120V	
Wattage	9W	
Light Output	765 LM	770 LM
Dimming	TRIAC	
L70	>50,000 Hrs	



Part Number	ELD6-13-5CCT-W-SM	ELD6-13-5CCT-W-BF
Dimension	Ø6"	
Trim	Smooth	Baffle
CRI	>90	
CCT	2700K/3000K/3500K/4000K/5000K Selectable	
Input Voltage	120V	
Wattage	13W	
Light Output	1,100 LM	1,180 LM
Dimming	TRIAC	
L70	>50,000 Hrs	



# CL16

## Power and CCT Selectable Cylinder



Part Number	CL16-40W-T1
CRI	90
CCT	3000K/3500K/4000K SELECT
Beam Spread	20°/30°/40°/50°
Input Voltage	120-277V
Wattage	20W/30W/40W SELECT
Efficacy	102 LM/W+
Light Output	4,362 LM
Dimming	0-10V
L70	>100,000 Hrs

### Mounting Options

### Bluetooth Control



Pendant Mount




Stem Mount



Surface Mount



### Beam Spread



**Keiton  
+ autani**




# EDF

## CCT Selectable Fire Rated Wafer Downlight




Part Number	EDF4-9W-T1	EDF6-12W-T1	EDF6-15W-T1
Dimension	Ø4"	Ø6"	Ø6"
CRI	90		
CCT	2700K/3000K/3500K/4000K/5000K Selectable		
Input Voltage	120V		
Wattage	9W	12W	15W
Efficacy	92 LM/W	110 LM/W	110 LM/W
Light Output	7,88 LM	1,271 LM	1,650 LM
Dimming	TRIAC		
L70	>100,000 Hrs		



# LSW

## Power and CCT Selectable Linear Stairwell Fixture



Part Number	LSW-2FT-30-TI-F-SL
CRI	>80
CCT	3000K/4000K/5000K Selectable
Input Voltage	120-277V
Wattage	30W/20W/15W/10W Selectable
Efficacy	137LM/W+
Light Output	4,071 LM
L70	>216,000 Hrs



Part Number	LSW-4FT-40-TI-F-SL
CRI	>80
CCT	3000K/4000K/5000K Selectable
Input Voltage	120-277V
Wattage	40W/25W/18W/12W Selectable
Efficacy	138LM/W+
Light Output	5,578 LM
L70	>100,000 Hrs



Part Number	LSW-8FT-80-TI-F-SL
CRI	>80
CCT	3000K/4000K/5000K Selectable
Input Voltage	120-277V
Wattage	80W/70W/60W/45W Selectable
Efficacy	136LM/W+
Light Output	11,406 LM
L70	>100,000 Hrs



# LSD

## Power and CCT Selectable Ultrasonic Stairwell Fixture



Part Number	LSD-2FT-15-TI-F-U1
Length	2FT
CRI	>80
CCT	3000K/4000K/5000K Selectable
Input Voltage	120-277V
Wattage	25W/20W/15W Selectable
Efficacy	137LM/W+
Light Output	5,538 LM
L70	>216,000 Hrs

Part Number	LSD-4FT-30-TI-F-U1
Length	4FT
CRI	>80
CCT	3000K/4000K/5000K Selectable
Input Voltage	120-277V
Wattage	50W/40W/30W Selectable
Efficacy	137LM/W+
Light Output	4,071 LM
L70	>216,000 Hrs

Part Number	LSD-4FT-45-TI-F-U1
Length	4FT
CRI	>80
CCT	3000K/4000K/5000K Selectable
Input Voltage	120-277V
Wattage	65W/55W/45W Selectable
Efficacy	138LM/W+
Light Output	5,578 LM
L70	>100,000 Hrs

Part Number	LSD-4FT-70-TI-F-U1
Length	4FT
CRI	>80
CCT	3000K/4000K/5000K Selectable
Input Voltage	120-277V
Wattage	90W/80W/70W Selectable
Efficacy	136LM/W+
Light Output	11,406 LM
L70	>100,000 Hrs



# VPL

## LED VAPORTIGHT GASKETED FIXTURE




Part Number	VPL-2FT-70P-T1
Length	2FT
CRI	>80
CCT	3500K/4000K/5000K Selectable
Input Voltage	120-277V
Wattage	90W/80W/70W Selectable
Efficacy	142LM/W+
Light Output	12,081 LM
L70	>71,000 Hrs

Part Number	VPL-2FT-80P-T1
Length	2FT
CRI	>80
CCT	3500K/4000K/5000K Selectable
Input Voltage	120-277V
Wattage	120W/100W/80W Selectable
Efficacy	142LM/W+
Light Output	16,968 LM
L70	>71,000 Hrs

Part Number	VPL-4FT-150P-T1
Length	4FT
CRI	>80
CCT	3500K/4000K/5000K Selectable
Input Voltage	120-277V
Wattage	200W/175W/150W Selectable
Efficacy	141LM/W+
Light Output	27,452 LM
L70	>156,000 Hrs

Part Number	VPL-4FT-185P-T1
Length	4FT
CRI	>80
CCT	3500K/4000K/5000K Selectable
Input Voltage	120-277V
Wattage	265W/225W/185W Selectable
Efficacy	141LM/W+
Light Output	37,339 LM
L70	>156,000 Hrs





# VPM

## LED VAPORTIGHT GASKETED FIXTURE



Part Number	VPM-4FT-50P-T1
Length	4FT
CRI	>80
CCT	3000K/4000K/5000K Selectable
Input Voltage	120-277V
Wattage	25W/20W/15W Selectable
Efficacy	137LM/W+
Light Output	5,538 LM
L70	>216,000 Hrs

Part Number	VVPM-8FT-100P-T1
Length	8FT
CRI	>80
CCT	3000K/4000K/5000K Selectable
Input Voltage	120-277V
Wattage	50W/40W/30W Selectable
Efficacy	137LM/W+
Light Output	4,071 LM
L70	>216,000 Hrs



# Exit Sign and Emergency Light Series



## LED Exit Sign

Part Number	EES01-R1-WH
Finish	White
Color	Red
Input Voltage	120-277V
Wattage	1.6W
Mounting	Ceiling/Wall

## Slim LED Exit Sign Combo

Part Number	ESC02-R1-WH-RC
Finish	White
Color	Red
Input Voltage	120-277V
Wattage	2.3W
Mounting	Ceiling/Wall
Options	Remote Load/Double Face



## Compact LED Exit Sign Combo

Part Number	ESC03-R1-WH-RC
Finish	White
Color	Red
Input Voltage	120V/277V
Wattage	4.2W
Mounting	Ceiling/Wall
Options	Remote Load/Double Face

## Edge Lit LED Exit Sign

Part Number	ESC04-S-C-R
Finish	White
Color	Red
Input Voltage	120V/277V
Wattage	4.2W
Mounting	Ceiling/Wall



## Dual Head Emergency Light

Part Number	EML01-WH-RC
Finish	White
Input Voltage	120V/277V
Wattage	2.4W
Mounting	Ceiling/Wall
Options	Remote Load

## Remote Head

Part Number	RH01-1H-WH	RH01-2H-WH
Finish	White	White
Input Voltage	120V/277V	120V/277V
Wattage	1.2W	2.4W
Mounting	Ceiling/Wall	Ceiling/Wall



# OUTDOOR LED LUMINAIRES





# Archer G2

## Architectural Area Light/Flood Light Combination



Part Number	AR2-100-T1	AR2-150-T1	AR2-300-T1
CRI	>80	>80	>80
CCT	3000K/4000K/5000K Selectable		
Input Voltage	120-277V/347-480V Optional		
Wattage	100W/80W/60W Selectable	150W/120W/100W Selectable	300W/240W/200W Selectable
Efficacy	149 LM/W+	150 LM/W+	149 LM/W+
Light Output	15,046 LM	22,036 LM	45,227 LM
Dimming	0-10V	0-10V	0-10V
Optics	Type II/Type III/Type IV/Type V		
Mounting	Arm/Trunnion/Yoke/Slipfitter		
L70	>100,000 Hrs	>100,000 Hrs	>100,000 Hrs

### Mounting Accessories



Slipfitter



Arm Mount



Trunnion Mount



Yoke Mount

### Control Options



Bluetooth PIR Sensor



PIR Sensor




Photocell


### Light Distribution Patterns

Area light is mounted at 20 ft. Calculation Area is set as 200x200 ft and the point spacing is 20x20 ft.


TYPE II (T2)




TYPE III (T3)



TYPE IV (T4)



TYPE V (T5)





# Clío G2

## Power and CCT Selectable LED Post Top




Part Number	PTV2-100P-T1
CRI	>80
CCT	3000K/4000K/5000K Selectable
Input Voltage	120-277V/347-480V Optional
Wattage	130W/100W/80W/60W Selectable
Efficacy	174LM/W+
Light Output	22,573 LM
Optics	Type III/Type V
L70	>100,000 Hrs


\*The fixture is already upgraded to meet DLC V6.0 requirements. Talk to sales team for submission schedule.

### Light Distribution Patterns


PTV2-100P-30-T3 @100W, 3000K with shield



PTV2-100P-T1-T3 @100W, 3000K



PTV2-100P-T1-T5 @100W, 3000K



### Accessories



3-Pin Photocell



7-Pin Photocell



Microwave Sensor



Remote



Tenon Reducer



Shorting Cap



Shield



# FORZA

## Beam Angle Adjustable Floodlight



Part Number	FLFZ-20W-TI-PH	FLFZ-35W-TI-PH
CRI	>80	>80
CCT	3000K/4000K/5000K Selectable	3000K/4000K/5000K Selectable
Input Voltage	120-277V	120-277V
Wattage	20W/15W/10W Selectable	35W/25W/15W Selectable
Efficacy	152LM/W+	150LM/W+
Light Output	3,059 LM	4,934 LM
Beam Spread	NEMA 7x6(90°), NEMA 6x6(75°), NEMA 5x5(55°)	
Mounting	Kunckle,Trunnion,Yoke	
L70	>100,000 Hrs	>100,000 Hrs



Part Number	FLFZ-60W-TI-PH	FLFZ-80W-TI-PH
CRI	>80	>80
CCT	3000K/4000K/5000K Selectable	3000K/4000K/5000K Selectable
Input Voltage	120-277V	120-277V/277-480V Optional
Wattage	60W/45W/35W Selectable	80W/70W/60W Selectable
Efficacy	154LM/W+	160LM/W+
Light Output	8,979 LM	12,105 LM
Beam Spread	NEMA 7x6(90°), NEMA 6x6(75°), NEMA 5x5(55°)	
Mounting	Kunckle,Trunnion,Yoke	
L70	>100,000 Hrs	>100,000 Hrs



Part Number	FLFZ-150W-TI-PH	FLFZ-320W-TI-PH
CRI	>80	>80
CCT	3000K/4000K/5000K Selectable	3000K/4000K/5000K Selectable
Input Voltage	120-277V/277-480V Optional	120-277V/277-480V Optional
Wattage	60W/45W/35W Selectable	320W/70W/60W Selectable
Efficacy	155LM/W+	149LM/W+
Light Output	22,195 LM	45,989 LM
Beam Spread	NEMA 7x6(90°), NEMA 6x6(75°), NEMA 5x5(55°)	
Mounting	Slipfitter,Trunnion,Yoke	
L70	>100,000 Hrs	>100,000 Hrs



Part Number	FLFZ-500W-TI-PH
CRI	>80
CCT	3000K/4000K/5000K Selectable
Input Voltage	120-277V/347-480V Optional
Wattage	500W/460W/420W Selectable
Efficacy	150LM/W+
Light Output	72,091 LM
Beam Spread	NEMA 7x6(90°), NEMA 6x6(75°), NEMA 5x5(55°)
Mounting	Slipfitter,Trunnion,Yoke
L70	>100,000 Hrs



# Ultra SP8

## Power Selectable Sports Light



Part Number	SP8-40P-50-M	SP8-50P-50-M	SP8-60P-50-M
CRI	70	70	70
CCT	5000K	5000K	5000K
Beam Spread	20°/30°/40°/60°/80°/120°	20°/30°/40°/60°/80°/120°	20°/30°/40°/60°/80°/120°
Input Voltage	200-480V	200-480V	200-480V
Wattage	200W/300W/400W SELECT	300W/400W/500W SELECT	400W/500W/600W SELECT
Efficacy	157 LM/W+	159 LM/W+	102 LM/W+
Light Output	61,583 LM	78,244 LM	98,068 LM
Dimming	0-10V	0-10V	0-10V
Mounting	Yoke/Slipfitter	Yoke/Slipfitter	Yoke/Slipfitter
L70	>100,000 Hrs	>100,000 Hrs	>100,000 Hrs

\*Also available in 4000K. Extra cost and lead time may apply.



Part Number	SP8-75P-50-M
CRI	70
CCT	5000K
Beam Spread	20°/30°/40°/60°/80°
Input Voltage	200-480V
Wattage	450W/600W/750W SELECT
Efficacy	164 LM/W+
Light Output	122,412 LM
Dimming	0-10V
Mounting	Yoke/Slipfitter
L70	>100,000 Hrs

\*Also available in 4000K. Extra cost and lead time may apply.



Part Number	SP8-100P-50-M	SP8-120P-50-M
CRI	70	70
CCT	5000K	5000K
Beam Spread	20°/30°/40°/60°	20°/30°/40°/60°
Input Voltage	200-480V	200-480V
Wattage	800W/900W/1000W SELECT	800W/1000W/1200W SELECT
Efficacy	162 LM/W+	162 LM/W+
Light Output	161,180 LM	192,370 LM
Dimming	0-10V	0-10V
Mounting	Yoke/Slipfitter	Yoke/Slipfitter
L70	>100,000 Hrs	>100,000 Hrs

\*Also available in 4000K. Extra cost and lead time may apply.



# ACE

## Power and CCT Selectable Tennis Court Sports Light



Part Number	ACE-500-T1-T4
CRI	80
CCT	3000K/4000K/5000K Selectable
Input Voltage	120-277V(277-480V Optional)
Wattage	500W/450W/400W Selectable
Efficacy	166 LM/W+
Light Output	78,043 LM
Dimming	0-10V
Distribution	T4 (T3 Optional)
L70	>100,000 Hrs



### Mounting Options



Arm Mount



Slipfitter



Trunnion Mount



Yoke Mount

### Control Options




Microwave Sensor




Photocell

### Beam Spread



ACE-500-T1-T3



ACE-500-T1-T4



# Vulcan V1

## High Mast Floodlight

Part Number	VUL1-50-XX	VUL1-60-XX	VUL1-75-XX
CRI	>70		
CCT	2700k/3000k/3500k/4000k/5000k		
Input Voltage	120-277V/200-480V Optional		
Wattage	500W	600W	750W
Efficacy	138-162 LM/W	133-151 LM/W	118-139 LM/W
Light Output	61,309-81,162 LM	76,342-89,734 LM	89,535-104,847 LM
Beam Spread	Symmetric 12°/15°/25°/50° Asymmetric 20°x40°/25°x105°/Medium/Narrow/Wide/Very Wide		
L70	>100,000 Hrs		

Part Number	VUL1-100-XX	VUL1-125-XX	VUL1-150-XX
CRI	>70		
CCT	2700k/3000k/3500k/4000k/5000k		
Input Voltage	120-277V/200-480V Optional		
Wattage	1000W	1250W	1500W
Efficacy	128-159 LM/W	121-164 LM/W	118-145 LM/W
Light Output	120,971-158,643 LM	142,841-201,677 LM	179,046-218,967 LM
Beam Spread	Symmetric 12°/15°/25°/50° Asymmetric 20°x40°/25°x105°/Medium/Narrow/Wide/Very Wide		
L70	>100,000 Hrs		

\*All models ship from China.

### ACCESSORIES



Visor



SPD




Louver




Adjustable Visor

### Distribution



# Vulcan V2

## Round High Mast Floodlight



Part Number	VUL2-20-XX	VUL2-30-XX
CRI	>70	
CCT	2700K/3000K/3500K/4000K/5000K	
Input Voltage	120-277V/277-480V Optional	
Wattage	200W	300W
Efficacy	147LM/W	147LM/W
Light Output	29,400 LM	44,100 LM
Beam Spread	Type II, Type III, Type IV, Type V	
L70	>100,000 Hrs	

Part Number	VUL2-45-XX	VUL2-50-XX
CRI	>70	
CCT	2700K/3000K/3500K/4000K/5000K	
Input Voltage	120-277V/277-480V Optional	
Wattage	450W	500W
Efficacy	147LM/W	147LM/W
Light Output	66,150 LM	73,500 LM
Beam Spread	Type II, Type III, Type IV, Type V	
L70	>100,000 Hrs	

Part Number	VUL2-60-XX	VUL2-75-XX
CRI	>70	
CCT	2700K/3000K/3500K/4000K/5000K	
Input Voltage	120-277V/277-480V Optional	
Wattage	600W	750W
Efficacy	147LM/W	147LM/W
Light Output	88,200 LM	110,250 LM
Beam Spread	Type II, Type III, Type IV, Type V	
L70	>100,000 Hrs	

\*All models ship from factory.

### ACCESSORIES



Visor



Photocell





# Guard Pack G2

## Power and CCT Selectable LED Full Cutoff Wall Pack




Part Number	WPGP-40M-T1	WPGP-80L-T1
CRI	>80	>80
CCT	3000K/4000K/5000K Selectable	3000K/4000K/5000K Selectable
Input Voltage	120-277V	120-277V
Wattage	40W/30W/20W/15W Selectable	80W/60W/50W/40W Selectable
Efficacy	161 LM/W+	166 LM/W+
Light Output	6,440 LM	12,792 LM
Dimming	0-10V	0-10V
Options	Photocell (Pre-installed) / EM	Photocell (Pre-installed) / EM
L70	>100,000 Hrs	>100,000 Hrs

### DUO Selectable Function

- Field-adjustable CCT**  
Selectable: 3000K/4000K/5000K
- Photocell ON/OFF**
- Field-adjustable wattage**  
4 Wattage selectable



### Distribution Pattern



### Control and EM Options



PIR Sensor



Emergency Battery Pack





## DEL

### Decorative Wall Pack with Emergency Battery Backup

Part Number	DEL-15-CS-PEI
CRI	80
CCT	3500K/4000K/5000K Selectable
Input Voltage	120-277V
Wattage	15W Selectable
Efficacy	138 LM/W+
Light Output	1,814 LM
Dimming	0-10V
Options	Integrated EM and Photocell
L70	>136,000 Hrs



## ECWP

### CCT Selectable Mini Wall Pack

Part Number	ECWP-30-TI-PH
CRI	80
CCT	3000K/4000K/5000K Selectable
Input Voltage	120-277V
Wattage	30W/20W/15W Selectable
Efficacy	149 LM/W+
Light Output	4,286 LM
Dimming	0-10V
Options	Integrated Photocell
L70	>100,000 Hrs



# WPDS

## Power and CCT Selectable LED Open Face Wall Pack



Part Number	WPDSN-80W-T1-G5
CRI	80
CCT	3000K/4000K/5000K Selectable
Input Voltage	120-277V
Wattage	80W/60W/40W Selectable
Efficacy	158 LM/W+
Light Output	12,519 LM
Dimming	0-10V
Options	Photocell(Pre-installed)/Sensor/EM
L70	>136,000 Hrs



Part Number	WPDSZ-120W-T1-G5
CRI	80
CCT	3000K/4000K/5000K Selectable
Input Voltage	120-277V
Wattage	120W/90W/60W/30W Selectable
Efficacy	142 LM/W+
Light Output	16,435 LM
Dimming	0-10V
Options	Photocell(Pre-installed)/Sensor/EM
L70	>136,000 Hrs

### Control and EM Options



PIR Sensor



Emergency Battery Pack



Emergency Battery Pack






## Sector

### Power and CCT Selectable Square Canopy Light

Part Number	SCP-75-T1
CRI	80
CCT	3000K/4000K/5000K Selectable
Input Voltage	120-277V
Wattage	75W/60W/50W/40W Selectable
Efficacy	156 LM/W+
Light Output	11,243 LM
Dimming	0-10V
Options	Sensor, EM
L70	>100,000 Hrs



## GRL

### General Purpose Round Garage Light

Part Number	GRL-70W-T1-F
CRI	80
CCT	3000K/4000K/5000K Selectable
Input Voltage	120-277V
Wattage	70W/60W/40W Selectable
Efficacy	167 LM/W
Light Output	10,710 LM
Dimming	0-10V
Options	Sensor, EM
L70	>136,000 Hrs





## IES FOOTCANDLE RECOMMENDATIONS

The following selected footcandle ranges represent the Illuminating Engineer Society's (IES) current illuminance recommendations. Individual applications will determine exact footcandle levels.

### Airplane Manufacturing

Drilling, riveting, screw fastening	75
Final assemble, hangar	100
Inspection	50-200
Welding	50

### Assembly

Rough easy seeing	20-50
Rough difficult seeing	50-100
Medium	100-200
Fine	200-500
Extra Fine	500-1000

### Auditoriums

Social activities	5-10
Assembly only	10-20
Exhibitions	10-20

### Automobile Manufacturing

Final assembly, finishing, inspecting	200
Body and chassis assembly	100
Body parts manufacturing	100
Frame assembly	50

### Banks

Lobby general	10-50
Writing areas	20-70
Teller stations, posting and keypunch	50-150

### Barber Shops

Beauty Parlors	50-100
Chemical Works	30

### Clothing Manufacturers

Receiving, storing, shipping, winding, measuring	20-50
Pattern making, trimming	50-100
Shops, marking	50-200
Cutting, pressing	100-200
Sewing, inspection	200-500

### Electrical Equipment Manufacturing

Impregnating	20-50
Insulating coil winding, testing	50-100

### Food Service Facilities

Dining areas, cashier	20-50
Cleaning	10-20
Dining	5-20
Food displays	30-100
Kitchen	50-100

### Foundries

Annealing furnaces	20-50
Cleaning	20-50
Core making	50-200
Inspection Fine	100-500
Medium	50-100
Molding	50-200
Pouring, sorting	50-100

### Garages-Motor Vehicles

Storage	5
Traffic lanes, parking garages	10
Service garage	10-20
Entrances	50
Repair area	50-100

### Gymnasiums

Assemblies	10
General exercise and recreation	30
Exhibitions, matches	50

### Hospitals

Rooms	10-30
Corridors	5-30
Emergency rooms	50-100
Operating rooms	100-200

### Hotels

Bathrooms	20-50
Bedrooms for reading	20-50
Corridors, elevators, and stairs	20-Oct
Front desk	50-100
Linen room, sewing	100-200
General	10-20
Lobby, general lighting	10-20
Reading and working areas	20-50

### Iron and Steel Manufacturing

Stock, hot top, checker, cellar, calcining	10-30
Building, slag pits, stripping yard	20
Control platforms, repairs, mixer building	30
Rolling mills	30-50
Shearing	50
Tin plate	50
Motor room, machine room	30
Inspection	100

### Laundries

Washing	20-50
Ironing	20-100

## Oceanside G3

### Power and CCT Selectable LED Bollard



#### EM BACKUP OPTIONS



#### 180 DEGREE SPILL SHIELD

This spill shield can be added to the bollard to provide a 180 degree of light coverage.



Part Number	BOR-FC-24W-TI-PH-G3	BOR-DC-24W-TI-PH-G3
CRI	80	80
CCT	3000K/4000K/5000K Selectable	3000K/4000K/5000K Selectable
Input Voltage	120-277V	120-277V
Wattage	24W/19W/14W Selectable	24W/19W/14W Selectable
Efficacy	125 LM/W	125 LM/W
Light Output	10,710 LM	10,710 LM
Dimming	0-10V	0-10V
Options	Sensor, EM	Sensor, EM
L70	>136,000 Hrs	>136,000 Hrs

\*The fixture is already upgraded to meet DLC V6.0 requirements. Talk to sales team for submission schedule.



# IES FOOTCANDLE RECOMMENDATIONS (continued)

<b>Library</b>		<b>Schools</b>	
Ordinary reading, stacks	20-50	Reading	20-100
Book repair and binding	20-50	Typing	20-100
Study & notes, cataloging, card files, check desk	20-100	Demonstrations	100-200
		Sewing	20-100
<b>Machine Shops</b>		<b>Sheet Metal Works</b>	
Rough bench	20-50	General	100
Medium bench, rough grinding, buffing	50-100	Tin plate inspection, galvanizing, scribing	100-200
Fine bench and work	200-500		
<b>Materials Handling</b>		<b>Stores</b>	
Loading trucking	10-20	Circulation area, stock room	
Picking stock, classifying	20-50	Merchandising, service	
Wrapping, packing, labeling	20-50	Merchandising, self-service	
<b>Offices</b>		<b>Textile Mills</b>	
Accounting	50-100	Cotton picking, carding, roving, spinning	50
Audio-visual areas	20-50	Beaming and slashing	150
Conference areas	20-70	Drawing	200
Corridors, Stairways	20(k)	Others	100
Drafting	50-200		
General and private offices	50-100	<b>Warehousing, Storage</b>	
Lobbies, lounges and reception areas	0-20	Inactive	5-10
Mail sorting	50-100	Active, rough, bulky	10-20
Offset printing and duplicating areas	20-50	Medium	20
Spaces with VDTs	75	Fine	20-50
<b>Paint Shop</b>		<b>Welding General</b>	
Spraying, rubbing, hand art, stencil	20-50		20-50
Fine hand painting and finishing	50-100	<b>Woodworking</b>	
<b>Paper Manufacturing</b>		Rough sawing and bench work	20-50
Beaters, grinding	50-100	Sizing, planning, rough sanding	20-50
Finishing, cutting	50-100	Medium quality bench work	20-50
Hand counting	50-100	Gluing, veneering, cooperage	20-50
Paper machine reel, inspection	100-200	Fine bench and machine work	50-100
Rewinder	100-200	Fine sanding and finishing	50-100
<b>Printing</b>		<b>Footnotes:</b>	
Photo engraving, etching	20-50	(a) Obtained with a combination of general	
Color inspecting	100-200	light plus specialized supplementary lighting	
Presses	50-100	(k) or not less than 1/5 the level in adjacent areas	
Proofreading	100-200		
Composing room	50-100		