



HELIX G4

LED ROUND HIGH BAY



HELIX G4
HIGH BAY

HELIX G4

LED ROUND HIGH BAY

DESCRIPTION

LED Round High Bay / 120-277VAC
input(347-480V Optional)/ Power Selectable*/ Ribbed Lens/
PC & Aluminum Shroud Available(Optional)/ PNP Sensor (Optional)

*Not for all models

APPLICATION

Warehouse/ Gym/Manufacturing/ Retail/ Distribution Center/ Hangar/ Workshop



PRODUCT FEATURES

- Power Selectable Technology: covering 3 wattage selections with 1 SKU(not for all models)
- Powder-coated aluminum housing, polycarbonate lens
- Optional PNP multifunction sensor, receptacle pre-installed
- 0-10V dimmable driver, featuring 12V AUX power tap
- RELOC options available*
- Ring-bolt mount included as default, pendant mount kit available*
- PC & Aluminum refractor offered*
- IP65 rated for wet location application
- Ambient operating temperature: -40°C(-40°F) to 55°C(131°F)
- DLC Premium listed

* optional accessories, order separately

PRODUCT SPECIFICATIONS

Catalog Part Number (For ordering)	Input Voltage	CCT	Nominal Wattage(W)	4000K			5000K			DLC QPL ID
				Watts (W)	Efficacy (LM/W)	Lumens (LM)	Watts (W)	Efficacy (LM/W)	Lumens (LM)	
HBUF-150P-40-G4 HBUF-150P-50-G4	120-277VAC	4K/5K Fixed	150	149	142	21,118	149	142	21,218	S-BK8SMV S-5Q460M
			120	118	147	17,382	118	148	17,441	
			90	89	153	13,634	89	154	13,680	
HBUF-200P-40-G4 HBUF-200P-50-G4	120-277VAC	4K/5K Fixed	200	199	142	28,215	199	142	28,241	S-MP2L8F S-7HLP27
			150	150	148	22,174	150	148	22,194	
			125	125	154	19,217	125	154	19,235	
HBUF-240P-40-G4 HBUF-240P-50-G4	120-277VAC	4K/5K Fixed	240	238	141	33,626	238	142	33,848	S-UBIX4T S-HE5X7B
			190	194	146	28,383	194	148	27,768	
			140	144	152	21,937	144	154	22,111	

HELIX G4


LED ROUND HIGH BAY

LUMEN MAINTENANCE


PROJECTED LUMEN MAINTENANCE

Ambient Test Temp	Reported Hrs	0 Hrs	25,000 Hrs	50,000 Hrs	TM-21-11 54,000	100,000 Hrs	L70 Hrs
25°C/77°F	>54,000	1	0.935	0.876	0.867	0.7693	136,000


INSTALLATION



Ring-bolt



PENDANT





CEILING MOUNT

* Ring-bolt comes standard, pendant mount and ceiling mount optional.
 * Check below see more info about mount kits.

HELIX G4

LED ROUND HIGH BAY

DIMENSIONS



PART#	WATTAGE	Diameter(D)	Height(H1)	Height(G2)
HBUF-150P-XX-G4	150W	11.2"	5.7"	7.2"
HBUF-200P-XX-G4	200W	12.8"	5.8"	7.4"
HBUF-240P-XX-G4	240W	12.8"	6.5"	7.7"
HBUF-300W-XX-G4	300W	15.4"	8"	8.4"

PHYSICAL FEATURES



1. 3-step power selectable
2. Ring-bolt mount comes standard, pendant mount(1/2 NPT) and ceiling mount available with optional mounting kit
3. Sensor receptacle pre-installed, multifunction sensor optional, can be easily field-installed


HELIX G4

LED ROUND HIGH BAY

PHOTOMETRIC SPECIFICATIONS

HBUF-150P-40-G4


Input Voltage(VAC): 120-277
 Nominal Wattage(W): 100
 System Wattage(W): 156.2
 Lumen Output(LM): 26900.7
 Efficacy(LM/W): 172
 CCT(K): 4000
 Color Rendering Index(CRI):
 Beam Angle:
 Spacing Criteria (0-180): 1.36
 Spacing Criteria (90-270): 1.44



Cone Of Light Tabulation		
Mounted Height (Feet)	Footcandles Beam Center	Diameter
15	57.9	43.5
17	45.2	46.5
20	32.6	52.5
23	24.7	54
25	20.9	57
28	16.7	61
30	14.5	64
Date Multipliers		
5000K		1.01
AL Reflector		0.95
PC Reflector		0.98
PC Reflector& Bottom Cover		0.85

HBUF-200P-50-G4


Input Voltage(VAC): 120-277
 Nominal Wattage(W): 100
 System Wattage(W): 193
 Lumen Output(LM): 32078.2
 Efficacy(LM/W): 166
 CCT(K): 5000
 Color Rendering Index(CRI):
 Beam Angle:
 Spacing Criteria (0-180): 1.36
 Spacing Criteria (90-270): 1.44



Cone Of Light Tabulation		
Mounted Height (Feet)	Footcandles Beam Center	Diameter
15	69.1	45
17	53.8	48
20	38.8	50.5
23	29.4	56
25	24.9	60
28	19.8	65
30	17.3	69
Date Multipliers		
5000K		0.98
AL Reflector		0.95
PC Reflector		0.98
PC Reflector& Bottom Cover		0.85

HBUF-240P-50-G4

Input Voltage(VAC): 120-277
 Nominal Wattage(W): 100
 System Wattage(W): 242.8
 Lumen Output(LM): 32566.7
 Efficacy(LM/W): 134
 CCT(K): 5000
 Color Rendering Index(CRI):
 Beam Angle:
 Spacing Criteria (0-180): 1.4
 Spacing Criteria (90-270): 1.36



Cone Of Light Tabulation		
Mounted Height (Feet)	Footcandles Beam Center	Diameter
15	70.1	46
17	54.6	49
20	39.4	56
23	29.8	58
25	25.2	60
28	21.6	59
30	17.5	64
Date Multipliers		
5000K		0.98
AL Reflector		0.95
PC Reflector		0.98
PC Reflector& Bottom Cover		0.85

HELIX G4

LED ROUND HIGH BAY

ADDITIONAL ACCESSORIES (SOLD SEPARATELY)

ATG CODE	MODEL NUMBER	DESCRIPTION
SQ	HB01DMS	Microwave Sensor for Helix G4, 12VDC
RQ	HB03R	Remote for HB01DMS and HB03DPR-A
EA	EMUFO-25170	EM Kit, 25W, Lithium Battery
EB	EMUFO-40170	EM Kit, 40W, Lithium Battery
PMK	PMK-HBUF-G4	Pendant and Ceiling Mount Kit
SRDP	SRD-HBUF-G4-D90	Poly Carbonate Shroud/Refractor for 100W-240W, 90°
SRDA	SRD-HBUF-G4-D90-A1	Aluminum Shroud/Refractor for 100W/150W, 90°
SRBC	SRD-HBUF-G4-BC	Bottom Cover for Poly Carbonate Shroud/Refractor
WG	WG-HBUF-G4	Wire Guard for 100W-240W
SR	HB03DPR-A	PIR sensor for Helix G4, 12VDC



EMUFO-25170



PMK-HBUF-G4




SRD-HBUF-G4-BC



SRD-HBUF-G4-D90-A1



SRD-HBUF-G4-D90



WG-HBUF-G4



HB03DPR-A



HB03R

ORDER FORMAT

Series	Wattage	CCT	Input	Gen	Finish	Sensor*	EM	Accessories*
HBUF				G4				
	200W= 200W	40= 4000K	Blank= 120-277VAC	G4= Gen4	Blank= Blank	SQ	EA	RQ
	240W= 240W	50= 5000K	V= 347-480VAC		W= White	NLC**	EB	WG
	300W= 300W							PMK
	150P= 150W/120W/90W Selectable							SRDP
	240P= 240W/190W/140W Selectable							SRDA
								SRBC

*See more details in ADDITIONAL ACCESSORIES sheet.

**Contact sales team for more details about NLC products.